



NOMENCLATURE

- AM AMMETER
- D DIODE
- FS FUEL SOLENOID
- DPS OIL PRESSURE SWITCH GAUGE
- OS OVERSPEED SWITCH (OPTIONAL)
- SC STARTER CONTACTOR
- SLR-I SAFETY LATCHING RELAY
- SLR-C SAFETY LATCHING RELAY COIL
- SI START STOP SWITCH
- SS START SOLENOID
- WTS WATER TEMPERATURE SWITCH GAUGE

NOTES:

1. WIRES MARKED A SEE DRWG. C-92400-1
2. WIRES MARKED B SEE DRWG. D-92416

ITEM	PART NO.	QUAN.	NAME	DETAILS	ITEM	PART NO.	QUAN.	NAME	DETAILS	ISSUE	REVISION	DATE	BY	AUTH.
9	A-91331-2	1	SLEEVING		17	B-24862-20	1	LEAD I.D. TAPE						
8	44791	2	CONNECTOR		16	B-24862-24	2	LEAD I.D. TAPE						
7	A-41569-2	1	SLEEVING		15	B-24862-75	4	LEAD I.D. TAPE						
6	4158	1	LUG		14	B-24862-122	4	LEAD I.D. TAPE						
5	A-48501-6	1	SLEEVING		13	B-24862-31	2	LEAD I.D. TAPE						
4	A-41569-4	1	SLEEVING		12	B-24862-76	4	LEAD I.D. TAPE						
3	B-52127-19	1	LEAD WIRE ASSEMBLY		11	B-24862-36	5	LEAD I.D. TAPE						
2	B-52125-149	1	LEAD WIRE ASSEMBLY		10	B-52126-73	1	LEAD WIRE ASSEMBLY						
1	B-52125-141	1	LEAD WIRE ASSEMBLY											

ALL DIMENSIONS GIVEN IN INCHES - WORK TO DIMENSIONS - DO NOT SCALE - SAMPLES MUST BE APPROVED BY DYNA TECHNOLOGY ENGINEERING DEPT. BEFORE PROCEEDING WITH PRODUCTION - TOLERANCES (UNLESS OTHERWISE SPECIFIED): FRACTIONS 2/1004 DECIMALS .005 PUNCHED HOLES .004 - .000 ANGLES 2:1

DRWN BY: D.M.W. DATE: 2-23-84 CBYD BY: EH DATE: APR 23 1984 APPR BY: EN DATE: 6-25-84 SCALE: _____

MATERIAL: _____

FRESH: _____

ARMY: D-92316 CONNECTION DIAGRAM D.C. MODEL: 50HDS-23EPT/B

Dyna TECHNOLOGY, INC. Le Center, MN 55057

C-92434-1