HONDA MOTOR CO., LTD.

EXECUTIVE ORDER U-U-001-1076 New Off-Road Small Spark-Ignition Engines at or Below 19 Kilowatts

Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095:

IT IS ORDERED AND RESOLVED: That the following engine and emission control systems produced by the manufacturer are certified for use in small off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGI	DISPLACEMENT (cc)		ENGINE CLASS		FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)	
2023	023 PHNXS.6882BA		688	4-stroke, ≥ 225 cc		Gasoline	
DURABILITY HOURS		SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION		
1000		EM			Walk-Behind Lawnmower, Riding Mower, Compressor, Pressure Washer, Generator Set, Commercial Turf		
ENGINE CODES/MODELS (rated power in kilowatt, kW)		See Attachment					

ABBREVIATIONS: EM=engine modification TWC/OC=three-way/oxidizing catalyst WUTWC/WUOC=warm-up TWC/OC O2S=oxygen sensor HO2S=heated O2S EGR=exhaust gas recirculation AIR=secondary air injection PAIR=pulsed AIR MFI=multi port fuel injection SFI=sequential MFI TBI=throttle body fuel injection DFI=direct fuel injection TC/SC=turbo/super charger CAC=charge air cooler 2(prefix)=parallel (2)(suffix)=in series ECM=engine control module

The following are the hydrocarbon plus oxides of nitrogen (HC+NOx), carbon monoxide (CO), and particulate matter (PM) emission standards (Title 13, California Code of Regulations, (13 CCR) Section 2403(b)), and certification emission levels for this engine family in grams per kilowatt-hour (g/kW-hr). Engines within this engine family shall have closed crankcases in conformance with Section 1054.115(a) of the "California Exhaust Emission Standards and Test Procedures for New 2013 and Later Small Off-Road Engines," adopted October 25, 2012.

*=not applicable	HC+NOx (g/kW-hr)	CO (g/kW-hr)	PM (g/kW-hr)	
STANDARD	8.0	549	*	
FAMILY EMISSION LEVEL	7.9	*	*	
CERTIFICATION LEVEL	7.5	321	*	

BE IT FURTHER RESOLVED: That the family emission level(s) (FELs), as applicable, is an emission limit declared by the manufacturer for use in the averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2403(e)(1) and 2407(a).

BE IT FURTHER RESOLVED: That for the listed engines, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2404 (emission control labels) and 13 CCR Sections 2405 and 2406 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Quarterly reports of engines produced in this engine family for sale in California shall be submitted to the Executive Officer no later than 45 days after the end of each calendar quarter.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed on this _____/2^{t_}_ day of July 2022.

Robin U. Lang, Chief

Johns Shi for

Emissions Certification and Compliance Division

Date: ___4/20/2022___

Engine Family: __PHNXS.6882BA__

For CARB Use	Only			
Executive Ord	er: L	J-U-00	1-10	76
Attachment	1	of	1	

Model Summary

	47.	48.	49.	50.	51.	52.	53.	54.	55.	56.
Worst Case	Model	Sales Code	Displacement	Bore/Stroke	Ignition Timing	Max Power	Rated Speed (RPM)	Rated Torque		Emission Control System
(Check One)	Designation		(cc)					·		·
X	2QH01A	50-State	688	78/72 mm	9° BTDC	15.5 kW	3600	48.3 N.m	2500	EM
	2QH02R	50-State	688	78/72 mm	9° BTDC	15.5 kW	3600	48.3 N.m	2500	EM
	2QK01A	50-State	688	78/72 mm	9° BTDC	16.5 kW	3600	48.3 N.m	2500	EM
	2QK02R	50-State	688	78/72 mm	9° BTDC	16.5 kW	3600	48.3 N.m	2500	EM
	2QV01A	50-State	688	78/72 mm	9° BTDC	15.5 kW	3600	48.3 N.m	2500	EM
	2QV02R	50-State	688	78/72 mm	9° BTDC	15.5 kW	3600	48.3 N.m	2500	EM
	2QX01A	50-State	688	78/72 mm	9° BTDC	16.5 kW	3600	48.3 N.m	2500	EM
	2QX02R	50-State	688	78/72 mm	9° BTDC	16.5 kW	3600	48.3 N.m	2500	EM
	2QH03R	50-State	688	78/72 mm	9° BTDC	15.5 kW	3600	48.3 N.m	2500	EM
	2QK03R	50-State	688	78/72 mm	9° BTDC	16.5 kW	3600	48.3 N.m	2500	EM