



DOUBLE WALL CONTAINMENT

Double wall tanks with 110% secondary containment.

UL142

Meets UL142 standard and is 100% leak tested at 3 psi.

INTERNAL Baffles

Internal baffles reduce sloshing and increase tank strength.

ELECTRONIC LEAK DETECTION

Electronic leak detection notifies of liquid in secondary containment.

FUEL LEVEL MONITORING

Electronic fuel level sender with mechanical fuel level indicator.



HEAVY DUTY LIFTING POINTS

Four point heavy duty lifting eyes.



STUB UP AREA

Electronic stub up area with removable panel.

CUSTOM TANKS

If our standard tanks don't meet your needs, we can order custom tanks to your fuel capacity specifications.

SPECIFICATIONS

Gal.	Compatible Models	Hours Full Load	Dimensions (L x W x H)	Approx. Dry Weight
54 ⁽¹⁾	DE Models	Varies	63" x 34" x 10"	150 lbs
54 ⁽¹⁾	DR12/20	29	63" x 34" x 11.5"	150 lbs
55	DR12/20	31	63" x 34" x 13"	500 lbs
110	DR12/20	61	63" x 34" x 23"	700 lbs
155	DR12/20	86	63" x 34" x 33"	850 lbs
100	DR45/65	24/22	84" x 41" x 13"	650 lbs
210	DR45/65	51/46	84" x 41" x 25"	1,050 lbs
495	DR45/65	76/68	84" x 41" x 36"	1,350 lbs
330	DR90	48	104" x 40" x 35"	1,400 lbs
495	DR90	71	142" x 40" x 35"	1,750 lbs
230	DR100/130/175	29/26/18	109" x 48" x 19"	1,300 lbs
415	DR100/130/175	53/47/33	109" x 48" x 36"	1,700 lbs
560	DR250/300/350	33/28/23	144" x 59" x 30"	2,500 lbs
845	DR250/300/350	50/42/34	144" x 59" x 36"	2,600 lbs

Notes: (1) The 54 Gallon fuel tanks are single wall, composite tanks.