

INTERNAL BAFFLES

Internal baffles reduce sloshing and increase tank strength.

ELECTRONIC LEAK DETECTION

Electronic leak detection notifies of liquid in secondary containment.

FUEL LEVEL GUAGE

Electronic fuel level sender with mechanical fuel level indicator.

HEAVY DUTY LIFTING POINTS

Four point heavy duty lifting eyes.

STUB UP AREA

Electrical connection, stub up area with removable panel.

CUSTOM TANKS

If our standard tanks don't meet your needs, we can order custom tanks to your fuel capacity specification. For example, fuel neck spill containment, seismic rating, vent extensions, high/low level float switch, or alarm panel.

SPECIFICATIONS

Gal.	Compatible Models	Hours Full Load	Dimensions (L x W x H)	Approx. Dry Weight
47 ⁽¹⁾	DE23/30/40/50/4040 Gen 4	22/12/15/11/11	70" x 30" x 15"	200 lbs
54 ⁽¹⁾	DR12/20	29	63" x 34" x 11.5"	275 lbs
55	DR12/20	31	63" x 34" x 13"	800 lbs
110	DR12/20	61	63" x 34" x 23"	1,030 lbs
155	DR12/20	86	63" x 34" x 33"	1,240 lbs
180	DR35/45/65/90	56/46/39/26	108" x 42" x 17"	1,700 lbs
320	DR35/45/65/90	100/82/70/46	108" x 42" x 29"	2,200 lbs
95	RP35	25	84" x 41" x 36"	1,350 lbs
200	RP50	55	104" x 40" x 35"	1,625 lbs
200	RP130	28	133" x 50" x 14"	1,100 lbs
230	DR100/130/175	29/26/18	108" x 48" x 19"	1,300 lbs
300	RP210	22	143" x 50" x 18"	1,400 lbs
415	DR100/130/175	53/47/33	108" x 48" x 31"	2,600 lbs
560	DR250/300/350	33/28/23	144" x 59" x 25"	3,200 lbs
845	DR250/300/350	50/42/34	144" x 59" x 35"	3,800 lbs
1,000	DR400/450/500/550/600	36/34/28/25/20	138" x 78" x 36"	4,400 lbs
1,340	DR400/450/500/550/600	48/46/38/34/27	250" x 78" x 24"	6,100 lbs
3,000	DR400/450/500/550/600	107/103/85/76/63	330" x 78" x 36"	9,240 lbs

Notes: (1) Fuel tank is not UL142 or UL2200 Listed. Units with these fuel tanks installed are not UL2200 compliant.

DIESEL FUEL TANKS



DOUBLE WALL CONTAINMENT

Double wall tanks with 110% secondary containment.

UL142

Meets UL142 standard and is 100% leak tested at 3 psi.