


DR400V4-XX/1 DR400V4-XX/2



Designed, engineered, and manufactured in our facility located in Le Center, Minnesota, equipped with modern engineering, fabrication and assembly capabilities.

Rugged Design

Engineered and built tough with powder coat paint galvanealed steel.

Full Load Tested

Every generator is 100% load tested in-house.

Volvo Engine

Reliable and durable, Volvo engines for standby power operations will ensure peace of mind, day after day.

**VOLVO
PENTA**



STAMFORD

VOLTS	POWER FACTOR	STANDBY			PRIME			CIRCUIT BREAKER
		WATTS	KVA	AMPS	WATTS	KVA	AMPS	
120/208 3-PH	0.8	400,000	500	1,388	360,000	450	1,250	1,300
120/240 3-PH	0.8	400,000	500	1,201	360,000	450	1,081	1,200
277/480 3-PH	0.8	400,000	500	601	360,000	450	541	600
346/600 3-PH	0.8	400,000	500	481	360,000	450	433	600

MOTOR STARTING (CODE G)	266 HP
DBA @ 7 METERS FULL LOAD	73
TOTAL HARMONIC DISTORTION	< 5%
FLOATING NEUTRAL	YES
FORKLIFT POCKETS	NO
ASSEMBLED IN	USA

EPA APPROVED	TIER III (STANDBY)
CARB APPROVED	TIER III (STANDBY)
TÜV CERTIFICATION	
CSA	YES
UL2200	YES
UNIT WARRANTY ⁽¹⁾	
STANDBY	2 YEAR/2000 HRS

ENGINE

ENGINE BRAND	VOLVO
ENGINE MODEL	TAD1353GE
TIER	III
ENGINE STARTER	24V ELECTRIC
ENGINE SPEED	1800 RPM
ENGINE CYLINDERS	6
ENGINE HP	585
FREQUENCY	60 HZ
ALTERNATOR	80 AMPS 24V
FLYWHEEL	14"
ROTATION	CCW
ASPIRATION	TURBOCHARGED
COOLANT	6 GAL
BORE/STROKE	131 mm x 158 mm

DISPLACEMENT/TYPE	12.78 L
RECOMMENDED OIL ⁽²⁾	5W-40 SAE
OIL CAPACITY	9.5 GAL
INJECTION PUMP	ELECTRIC INJECTORS
GOVERNOR	ISOCRONOUS
COMPRESSION RATIO	18.1:1
FAN TYPE	PUSHER
INTAKE AIR CONSUMPTION	1102 CFM
RADIATOR COOLING AIR	-
EXHAUST FLOW	2790 CFM
EXHAUST OUTLET SIZE	5"
STARTING AIDES	-
STARTING TEMP W/BLOCK HEATER	-13° F

FUEL

TYPE	ASTM D975 NO-2D DIESEL
FUEL CONSUMPTION	GAL/HR
100%	29.1
75%	22.3
50%	15.3
25%	8.5

OPTIONAL FUEL TANK	L x W x H
1000 GAL - OPEN SKID	138" x 78" x 34"
1340 GAL - HOUSED	236" x 78" x 24"
3000 GAL - HOUSED	330" x 78" x 36"

GENERATOR END

GENERATOR END BRAND	STAMFORD
GENERATOR END MODEL	S4L1D-G4
WINDING	
3-PHASE	311 - 12 LEAD
600V	-17 - 12 LEAD
VOLTAGE REGULATION	AVR +/- 1%
AVR TYPE	MX341
TEMPERATURE RISE	125/40°C
TYPE	REVOLVING FIELD
BRUSHLESS	YES

SPEED	1800 RPM
ROTOR	2/3 PITCH
WINDINGS	100% COPPER
STATOR WINDING	DOUBLE LAYER LAP
COUPLING	DIRECT/FLEXIBLE DISC
BEARINGS	SINGLE (MAINTENANCE FREE)
EFFICIENCY PEAK	93.6
INSULATION	CLASS H
INGRESS PROTECTION	IP23

DERATES

ABOVE SEA LEVEL	
> 3,200 FT - 6,500 FT	1.25% EVERY 1,500 FT
> 6,500 FT	7.5% EVERY 1,600 FT

MAX OPERATING TEMPERATURE	122° W/O TEMPERATURE DERATE
------------------------------	--------------------------------

BLOCK HEATER

VOLTS	120
WATTS	3,000
AMPS	25

THERMOSTAT	
ON	100° F
OFF	120° F

BATTERY

DC SYSTEM	24V
BATTERY RACK/CABLE	INCLUDED

BATTERY CHARGER	5 AMP
REQUIRED BATTERIES ⁽³⁾	GROUP 4D 1200 CCA


DSE 7310 MKII CONTROLLER

ENGINE DISPLAY/PROTECTION	
ENGINE RPM	YES
LOW OIL PRESSURE	YES
HIGH COOLANT TEMP	YES
LOW COOLANT	YES
OVER/UNDER SPEED	YES
OVER CRANK	YES
CAN ECU SHUTDOWN	YES
GENSET DISPLAY/PROTECTION	
VOLTAGE (L-N & L-L)	YES
OVER/UNDER VOLTAGE	YES
FREQUENCY	YES
OVER/UNDER FREQUENCY	YES
AMP DISPLAY/SHUTDOWN	YES
PHASE IMBALANCE	DISABLED
KW, KVA, KVARH DISPLAY	YES
KWH, KVAH, KVARH DISPLAY	YES
GENERATOR PHASE SEQUENCE	OPTIONAL

ADDITIONAL DISPLAYS/PROTECTIONS	
EXTERNAL E-STOP	YES
BATTERY VOLTAGE	YES
BATTERY OVER/UNDER VOLTAGE	YES
COMMUNICATIONS	
USB CONNECTABLE	YES
RS232/RS485	YES
NFPA ANNUNCIATOR	OPTIONAL
REMOTE DISPLAY PANEL	OPTIONAL
ETHERNET/MODEM	OPTIONAL
ADDITIONAL FEATURES	
AUDIBLE ALARM	YES
ENGINE EXERCISER	YES
MAINTENANCE INTERVAL TIMER	OPTIONAL
LOAD SHEDDING/DUMMY	OPTIONAL
CONFIGURABLE INPUTS	4 (EXPANDABLE)
CONFIGURABLE OUTPUTS	4 (EXPANDABLE)
EVENT LOG	250

SHIPPING

SHIPPING DIMENSIONS (L x W x H)	
HOUSED	236" x 78" x 99"
NARROW SKID	126" x 48" x 72"
SHIP WEIGHT	
OPEN SKID	8,950 LBS
HOUSED	11,500 LBS
FREIGHT CLASS	70




OPTIONAL ACCESSORIES

BATTERIES - (2) GROUP 4D 1200 CCA
BATTERY HEATER
MIMIC PANEL

REMOTE MONITORING
NFPA 110 LEVEL 1 UPGRADE
DSE8610 WITH PARALLELING CONTACTOR

NOTES:
 (1) For more warranty information, see operator's manual.
 (2) The recommended oil is for normal applications.
 See operator's manual for more oil recommendations.
 (3) 2 batteries are required. Batteries not included.
 Specifications are subject to change without notice.



Sales: 507-357-6821
 Service: 507-357-6831

